



GROUND PRO Thixotropic Bitumen Compound

15kg

Product Code: **LM00013**

Pallet Quantity: **36**

GROUND PRO Thixotropic Bitumen Compound is a cold hand applied, thixotropic bitumen emulsion formulated for the effective sealing of vertical joints.

Primarily designed for sealing and protecting newly laid asphalt and macadam substrates, GROUND PRO Thixotropic Bitumen Compound can also be used as a multi-purpose tack coating primer.

KEY FEATURES

- 15kg Tub
- Cold hand applied thixotropic bitumen emulsion designed for sealing vertical joints
- Ideal for diagonal & longitudinal vertical joints, kerb channels, patch repair, trench reinstatements, drainage/manhole frames & exposed ironwork
- Can also be used as a tack-coat on small areas

SPECIFICATION

Volume	15kg
Packaging	Re-sealable plastic tub
Coverage Rate	Vertical Joints: 1mm thick coating covers approx. 1.5m ² 50mm Joints: 1x 15kg Tub covers approx. 200 Linear Meters
Equipment/Materials	Soft fibre or Turks head brush Water

CONFORMITY

Complies with BS 594987

PREPARATION

Ensure surface is dry, clean and free from dirt, oil, grease, weeds, and loose materials.

Thixotropic Bitumen emulsion should not be applied at temperatures below 5°C.

APPLICATION INSTRUCTIONS

1. Dampen brush with clean water prior to first use to loosen the bristles. Remove any excess water so the brush is damp but not saturated.
2. Open product lid and dip the brush into the Thixotropic Bitumen Emulsion until it is completely coated.
3. Apply evenly in one direction at a time until the entire joint is covered.

DRYING TIME

Surfacing can commence within 15 minutes unless conditions are significantly cold, wet or humid.

Drying time can be hastened with the application of hot material.

STORAGE

Do not stack heavy items on top of the product and store in a dry location, at a minimum temperature of 5°C.

6 Months storage life in sealed container.

