EVO TOOL SURESTRIKE Concrete Mould Release Oil

5L

Product Code: HT02820

Pack Quantity: 1

EVO TOOL SURESTRIKE is a high-performance, plant-based release agent formulated from natural vegetable oils and polymeric extracts.

Designed for general site and precast applications, it creates a reliable barrier between formwork and concrete, delivering a smooth, uniform finish. Enhanced with surfactants, it helps minimise blowholes and ensures clean, stain-free results across a wide range of mould surfaces.

PRODUCT DESCRIPTION

EVO TOOL SURESTRIKE is a blend of natural Vegetable oils and naturally occurring polymeric extracts for general site and precast yard use. It achieves a top-quality concrete finish in most situations and with most common mould surfaces. Release is achieved by the formation of a physical barrier between the formwork surface and the concrete. Surfactants present in EVO TOOL SURESTRIKE help to eliminate blowholes and provide a clean, uniform, and non-stained surface.

KEY FEATURES

- Facilitates easy formwork release
- Provides uniform stain-free concrete surfaces
- Minimises incidence of surface air voids
- Reduces form cleaning to a minimum
- Highly resistant to removal by rain showers or foot traffic
- High coverage rate provides economic usage
- Suitable for use on all types of formwork in all climatic conditions
- Easy application by spray, brush or swab
- Suitable for use on sealed or unsealed timber formwork
- Forms may be stripped early when other factors permit
- Ideal for achieving release from multi-planed features e.g. trapezoidal ribs, cone shaped column heads etc
- Suitable for use with white or standard OPC concrete finishes
- Fully compatible with the subsequent application of silicone or similar surface treatments when used as recommended
- VOC Free

COVERAGE

A thin coating gives a coverage between 30 to 40m^2 per litre depending upon surface porosity. Excessive application of release agents can be detrimental to the concrete surface finish: therefore care should therefore be taken to ensure that EVO TOOL SURESTRIKE is applied as recommended. as this will achieve optimum performance and maximum economy.

STORAGE

Store between 5 and 30°C. Protect from frost and excessive heat.

SHELF LIFE

12 months in its sealed container

CONSIDER IT DONE.
WWW.CIDGROUP.CO.UK | SALES@CIDGROUP.CO.UK | 0113 201 1340
CID Trading LTD, Friden House, Unit 1, Clayton Wood Bank, Horsforth, Leeds, LS16 6QZ

HEALTH & SAFETY

Prolonged physical contact should be avoided and personal and environmental hygiene encouraged in common with the use of all mould release agents. Where contact with skin occurs, the material should be removed with soap and water. If splashes affect eyes, they should be bathed immediately with copious quantities of clean water and if discomfort persists medical attention should be sought without deiay.

See separate Safety Data Sheet for further information.

APPLICATION

After preparation of formwork and any necessary sealing. apply thinly, by spray, brush or swab prior to each concrete pour and as near to time of placement of concrete as practical conditions permit. Timber and other porous forms which have not been treated with Plastic Formwork Coating or other suitable sealer should initially be treated with a double coot of EVO TOOL SURESTRIKE, the first applied heavily and allowed to stand for maximum absorption before the second is applied in normal manner. On vertical forms any excess material accumulating at the bottom of the form should be removed.

VOLUMES AVAILABLE

CODE	VOLUME
HT02820	5L
HT02821	20L

CONSIDER IT DONE.
WWW.CIDGROUP.CO.UK | SALES@CIDGROUP.CO.UK | 0113 201 1340
CID Trading LTD, Friden House, Unit 1, Clayton Wood Bank, Horsforth, Leeds, LS16 6QZ