



GROUND PRO Rapid Setting Postfix

20kg

Product Code: **LM00906**

Pallet Quantity: **70**

GROUND PRO 20kg Rapid Setting Postfix is a high-performance, fast-setting solution designed for quick and reliable post installation. With a specialised aggregate mix for strong initial support, it sets in under five minutes - making it ideal for efficient outdoor projects. Each 20kg bag is conveniently measured for one post, ensuring easy use with minimal waste. Supplied in durable plastic packaging and suitable for outside storage, it's a convenient and dependable choice.

APPLICATION

- Please refer to application instructions detailed on the packaging
- Recommended for use between temperatures of 5°C and 25°C
- Do not use when ground is frozen at temperatures below 5°C
- Typical set time between 5 and 10 mins
- Typical 28-day strength of 20N/mm²

KEY FEATURES

- 20kg Bag
- Fast-setting formula
- Sets in under five minutes
- 20kg bag coverage: 1 bag to 1 post
- Aggregate mix to ensure good initial support for the post
- Supplied in plastic packaging
- Suitable for outside storage
- Priced per pallet of 70

GUIDANCE FOR USE

- Dig a hole to the required size for the post
- Add water to the prepared hole
- Add water to the hole to one third of its depth
- Add Postfix evenly around the base of the post
- Add additional water to dry powder still visible
- Adjust the post into position and support appropriately for approximately 10 minutes until secure

STORAGE

Bags should be stored unopened, clear of the ground, in cool dry conditions and protected from excessive draft and all sources of moisture.

HEALTH AND SAFETY

Contact with cement may cause skin, eye and respiratory irritation, severe burns and dermatitis. Always wear suitable personal protective equipment (PPE) and refer to the full Material Safety Data Sheet for further information.

Approximate guide

Post size	Hole Depth (mm)	Hole Width (mm)	Approximate no. of bags
75 x 75mm (3")	600	200	3/4 - 1
100 x 100mm (4")	600	250	1 - 2
150 x 150mm (6")	750	300	2
200 x 200mm (8")	900	400	3

Adjust quantities as needed for non-standard hole shapes or additional requirements.

