

GROUND PRO Bitumen Tack Coat Sealer

750ml

Product Code: LM00270

Pack Quantity: 1

Bitumen cold joint sealer & tack coat spray is designed to be applied onto vertical edges and the surface base before the application of asphalt. It will increase the bond of the material to the substrate and waterproof the area. This will significantly enhance the reinstatement's performance by preventing the ingress of water and freeze/thaw effect.

DIRECTIONS FOR USE

- Shake can vigorously before use
- Ensure that the area being sealed is clear of all standing water and loose particles
- Turn the can upside down and spray along vertical edge of prepared excavation
- Cover the edge to be sealed with long strokes from a distance of 200-300mm making sure to cover entire surface
- After use hold the can upright and spray for a few seconds to clear the bitumen from the spray valve

Note: Not to spray in the wind. Dispose of contents/ container in accordance with local regulations.

HEALTH AND SAFETY

CONTAINS:

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics, Fatty acids, reaction products with N-(2-aminoethyl) piperazine. May produce an allergic reaction.container in accordance with local regulations.

DANGER:

- Extremely flammable aerosol.
- May cause damage to organs through prolonged or repeated exposure.
- Harmful to aquatic life with long lasting effects.
- Keep out of reach of children.
- Do not breathe vapour/ spray.
- Use only outdoors or in a well-ventilated area.
- Repeated exposure may cause skin dryness or cracking.
- Restricted to professional users.



IF ON SKIN:

Wash with plenty of water.
If skin irritation occurs: Get medical advice/attention.

IF IN EYES:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

CAUTION:

Pressurised container: May burst if heated. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

CONSIDER IT DONE.
WWW.CIDGROUP.CO.UK | SALES@CIDGROUP.CO.UK | 0113 201 1340
CID Trading LTD, Friden House, Unit 1, Clayton Wood Bank, Horsforth, Leeds, LS16 6QZ

SHELF LIFE

24 months from the date of manufacture. Store aerosol cans upright in a cool, dry, and well-ventilated area at temperatures between +5°C and +25°C. Keep them away from direct sunlight, hot surfaces, and ignition sources and do not expose to temperatures exceeding 50 °C.

CONSIDER IT DONE.
WWW.CIDGROUP.CO.UK | SALES@CIDGROUP.CO.UK | 0113 201 1340
CID Trading LTD, Friden House, Unit 1, Clayton Wood Bank, Horsforth, Leeds, LS16 6QZ