

# FIRECHIEF XTR LIGHTWEIGHT STEEL CO2 EXTINGUISHERS


Product Code: FXC2S, FXC5S



The Firechief range is widely recognised and trusted by resellers and end-users alike. In the 12 years that Firechief extinguishers have been established in the UK fire market, they have become synonymous with quality and reliability.

- Lightweight Steel construction
- Squeeze grip operation
- Corrosion resistant finish
- Harmless to machinery
- Approved to BSEN3
- Supplied with bracket
- FXC2S supplied with frost free horn
- 5 year guarantee

	FXC2S	FXC5S
Capacity	2kg	5kg
Fire Rating	34B	89B
MED Approval	Yes	Yes
35kV Dielectric	N/A	N/A
LPCB Cert No	1093a/35	1093a/37
Kitemark No	558897	558897
Height (mm)	580	660
Diameter (mm)	110	235
Total width (mm)	160	310
Filled weight (kg)	6.3	13.2
Throw range (m)	6.2	7
Discharge time (secs)	21	22
Working Pressure (bar)	150	150
Temp. Range	-30/+60	-30/+60
Refill code	N/A	N/A
Number per pallet	96	40



Licence No. KM35021

## MATERIAL SAFETY DATA SHEET



Phone: 0330 999 2233  
 Email: [info@firedepot.co.uk](mailto:info@firedepot.co.uk)  
[www.firedepot.co.uk](http://www.firedepot.co.uk)

## PRODUCT: Carbon Dioxide

### 1.IDENTIFICATION OF THE PREPARATION AND OF THE COMPANY

- 1.1 IDENTIFICATION OF THE PREPARATION: Carbon Dioxide
- 1.2 COMPANY IDENTIFICATION Fire Depot  
Sentura House  
3 Lands End Way  
OAKHAM  
Rutland  
LE15 6RB
- 1.4 EMERGENCY TELEPHONE: 01752 770478

### 2.COMPOSITION/INFORMATION ON INGREDIENTS

Substance name: Contents CAS No EC No Annex No Classification  
Carbon dioxide 100% 124-38 204-696-9 ----  
Contains no other components or impurities which will influence the classification of the product.

### 3.HAZARDS IDENTIFICATION

Hazards identification: Liquefied gas.  
In high concentrations may cause asphyxiation

### 4.FIRST AID MEASURES

- Inhalation: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Low concentrations of CO<sub>2</sub> cause increased respiration and headache. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin/eye: Immediately flush eyes thoroughly with water for at least 15 minutes.
- Contact: In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Ingestion: Ingestion is not considered a potential route of exposure.

### 5.FIRE-FIGHTING MEASURES



Phone: 0330 999 2233  
Email: [info@firedepot.co.uk](mailto:info@firedepot.co.uk)  
[www.firedepot.co.uk](http://www.firedepot.co.uk)

Not applicable as carbon dioxide is non-flammable and non combustible.  
Exposure to fire may cause containers to rupture/explode.

## 6.ACCIDENTIAL RELEASE MEASURES

Personal precautions: Evacuate area.  
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
Ensure adequate air ventilation.

Environmental precautions: Try to stop release.  
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Methods for cleaning up: Ventilate area.

## 7.HANDLING AND STORAGE

**Storage Handling:** Keep container below 50°C in a well ventilated place.  
Suck back of water into the container must be prevented.  
Do not allow backfeed into container.  
Use only properly specified equipment which is suitable for this product,  
Its supply pressure and temperature. Contact your gas supplier if in doubt.  
Refer to supplier's container handling instructions.

## 8.EXPOSURE CONTROLS/PERSONAL PROTECTION

**Personal protection:** Ensure adequate ventilation.

**Occupational Exposure Limits**

Carbon dioxide : TLV©-TWA (ppm): 5000  
Carbon dioxide : TLV©-STEL (ppm): 30000  
Carbon dioxide : OEL (UK)-LTEL (ppm): 5000  
Carbon dioxide : OEL (UK)-STEL (pm): 15000  
Carbon dioxide : MAK – Germany (ppm): 5000

## 9.PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20°C: Liquefied gas.  
Colour: Colourless.  
Odour: No odour warning properties.



Phone: 0330 999 2233  
Email: [info@firedepot.co.uk](mailto:info@firedepot.co.uk)  
[www.firedepot.co.uk](http://www.firedepot.co.uk)

Molecular weight: 44  
Melting point (°C): -56.6  
Boiling point (°C): -78.5 (s)  
Critical temperature (°C): 30  
Vapour pressure (20°C): 57.3bar  
Relative density, gas (air=1): 1.52  
Solubility in water (mg/l): 2000  
Flammability range (vol% in air): Non flammable  
Other data: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

## 10.STABILITY AND REACTIVITY

Stability and reactivity: Stable under normal conditions

## 11.TOXICOLOGICAL INFORMATION

Toxicity information: In high concentrations cause rapid circulatory insufficiency. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness.

## 12.ECOLOGICAL INFORMATION

Ecological effects information: When discharged in large quantities may contribute to the Greenhouse effect.  
Global warming factor (CO2=1): 1

## 13.DISPOSAL CONSIDERATIONS

General: Do not discharge into any place where its accumulation could be dangerous.  
Discharge to atmosphere in a well ventilated place.  
Discharge to atmosphere in large quantities should be avoided.  
Contact supplier if guidance is required.

## 14.TRANSPORT INFORMATION

When transported in a cartridge or side cylinder the cylinder is considered a class 2.2 hazard. The proper shipping name shall be CARBON DIOXIDE and the number is UN 1013.



Phone: 0330 999 2233  
Email: [info@firedepot.co.uk](mailto:info@firedepot.co.uk)  
[www.firedepot.co.uk](http://www.firedepot.co.uk)

When transported in a stored pressure or cartridge type fire extinguisher, the fire extinguisher is considered a class 2.2 hazard. The proper shipping name shall be FIRE EXTINGUISHER and the number is UN 1044

## 15.REGULATORY INFORMATION

EC Classification:	Not included in Annex 1. Not classified as dangerous preparation/substance.
EC Labelling:	No EC labelling required.
Symbol(s):	None
R Phrase(s):	None
S Phrase(s):	None

## 16.OTHER INFORMATION

<b>Training advice:</b>	Asphyxiant in high concentrations. Keep container in a well-ventilated place. Do not breathe the gas. Contact with liquid may cause cold burns/frostbite.
-------------------------	--

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. Information source (data sheet) original chemical supplier Air Liquide. The information given is designed only as guidance for safe handling, uses processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.



Phone: 0330 999 2233  
Email: [info@firedepot.co.uk](mailto:info@firedepot.co.uk)  
[www.firedepot.co.uk](http://www.firedepot.co.uk)